

A close-up, low-angle shot of a red Ferrari truck-mounted crane boom. The boom is the central focus, extending from the bottom left towards the top right. It features black hydraulic cylinders and various mechanical joints. The background is a solid, vibrant red. The overall composition is dynamic and emphasizes the industrial strength of the equipment.


Ferrari®

New Age

**NEW
CRANE
LINE**

**TRUCK
Mounted
CRANES**

13 - 16 tm Families



Perfect cost:
performance solution

7130B

A1

kg	2770	1955
m	4,49	6,29

A2

kg	2635	1820	1400	1015	755	560
m	4,49	6,29	8,09	10,31	12,29	14,34

A3

kg	2500	1700	1285	1020	755	560	410
m	4,57	6,37	8,17	10,15	12,29	14,34	16,44

A4


kg	2380	1595	1180	910	755	560	410
m	4,66	6,46	8,26	10,24	12,22	14,34	16,44

A5

kg	2265	1500	1090	825	665	560	410
m	4,73	6,53	8,33	10,31	12,29	14,34	16,44

7160B

Configuration	kg	m
A1	3525, 2490	4,49, 6,34
A2	3345, 2320, 1785, 1310, 980, 740	4,49, 6,29, 8,09, 10,31, 12,29, 14,34
A3	3180, 2185, 1655, 1310, 980, 740, 535	4,57, 6,37, 8,17, 10,15, 12,29, 14,34, 16,44
A4	3035, 2055, 1525, 1190, 980, 740, 535	4,66, 6,46, 8,26, 10,24, 12,22, 14,34, 16,44
A5	2905, 1935, 1415, 1085, 875, 740, 535	4,73, 6,53, 8,33, 10,31, 12,29, 14,34, 16,44



High performance articulated
double linkage cranes

7131C

A2

kg	2620	1780	1350	975	720	525
m	4,58	6,53	8,48	10,86	12,91	15,06

A3

kg	2490	1660	1235	975	720	525	375
m	4,66	6,61	8,56	10,61	12,91	15,06	17,21

A4

kg	2360	1550	1130	870	720	525	375	280
m	4,75	6,7	8,65	10,7	12,75	15,06	17,21	19,31

A5

kg	2245	1445	1030	775	625	525	375	280
m	4,83	6,78	8,73	10,78	12,83	14,98	17,21	19,31

A6

kg	2140	1350	940	690	535	435	375	280
m	4,91	6,86	8,81	10,86	12,91	15,06	17,21	19,31

7143C

Configuration	Segment	Weight (kg)	Length (m)
A2	1	2700	4,58
	2	1850	6,53
	3	1420	8,48
	4	1045	10,86
	5	780	12,91
	6	575	15,06
A3	1	2560	4,66
	2	1730	6,61
	3	1300	8,56
	4	1045	10,61
	5	780	12,91
	6	575	15,06
A4	1	2435	4,75
	2	1615	6,7
	3	1190	8,65
	4	930	10,7
	5	780	12,75
	6	575	15,06
A5	1	2310	4,83
	2	1510	6,78
	3	1085	8,73
	4	830	10,78
	5	675	12,83
	6	575	14,98
A6	1	2205	4,91
	2	1415	6,86
	3	995	8,81
	4	740	10,86
	5	585	12,91
	6	480	15,06

7153C

A2

kg	3040	2075	1575	1165	870	655
m	4,58	6,53	8,48	10,86	12,91	15,06

A3

kg	2900	1950	1460	1165	870	655	485
m	4,66	6,61	8,56	10,61	12,91	15,06	17,21

A4

kg	2765	1835	1350	1050	870	655	485	395
m	4,75	6,7	8,65	10,7	12,75	15,06	17,21	19,31

A5

kg	2640	1730	1250	955	775	655	485	395
m	4,83	6,78	8,73	10,78	12,83	14,98	17,21	19,31

A6

kg	2530	1635	1160	865	685	565	485	395
m	4,91	6,86	8,81	10,86	12,91	15,06	17,21	19,31

7161C

Configuration	Weight (kg)	Length (m)
A2	3345, 2280, 1735, 1275, 950, 710	4,58, 6,53, 8,48, 10,86, 12,91, 15,06
A3	3185, 2140, 1595, 1275, 950, 710, 530	4,66, 6,61, 8,56, 10,61, 12,91, 15,06, 17,21
A4	3040, 2010, 1475, 1155, 950, 710, 530, 400	4,75, 6,7, 8,65, 10,7, 12,75, 15,06, 17,21, 19,31
A5	2900, 1895, 1365, 1040, 845, 710, 530, 400	4,83, 6,78, 8,73, 10,78, 12,83, 14,98, 17,21, 19,31
A5	2775, 1790, 1265, 945, 745, 615, 530, 400	4,91, 6,86, 8,81, 10,86, 12,91, 15,06, 17,21, 19,31
A6	2775, 1790, 1265, 945, 745, 615, 530, 400	4,91, 6,86, 8,81, 10,86, 12,91, 15,06, 17,21, 19,31

7173C

Configuration	Weight (kg)	Length (m)
A2	3430	4,58
A3	3270	4,66
A4	3120	4,75
A5	2985	4,83
A6	2855	4,91

7183C

A2

kg	3775	2575	1965	1460	1105	845
m	4,58	6,53	8,48	10,86	12,91	15,06

A3

kg	3605	2435	1830	1460	1105	845	645
m	4,66	6,61	8,56	10,61	12,91	15,06	17,21

A4


kg	3450	2305	1705	1340	1105	845	645	510
m	4,75	6,7	8,65	10,7	12,75	15,06	17,21	19,31

A5

kg	3305	2185	1590	1230	995	845	645	510
m	4,83	6,78	8,73	10,78	12,83	14,98	17,21	19,31

A6

kg	3175	2080	1490	1130	900	745	645	510
m	4,91	6,86	8,81	10,86	12,91	15,06	17,21	19,31



Telescopic cranes,
compact and easy to use

7130D

A2

Category	kg	m
1	5290	2,48
2	3005	4,28
3	2095	6,08

A3

Category	kg	m
1	5065	2,56
2	2865	4,36
3	1975	6,16
4	1475	8,14


A4

Category	kg	m
1	4855	2,64
2	2735	4,44
3	1860	6,24
4	1375	8,22
5	1095	10,20

7162D

The figure consists of three diagrams, A2, A3, and A4, each showing a horizontal bar with a red section on the left and a white section on the right. The red section is divided into three segments, and the white section is divided into three segments. The dimensions are given in kg and m.

Diagram	kg	m
A2	6630, 3780, 2645	2,48, 4,28, 6,08
A3	6355, 3620, 2510, 1880	2,56, 4,36, 6,16, 8,14
A4	6050, 3440, 2360, 1750, 1395	2,64, 4,44, 6,24, 8,22, 10,20



Short boom articulated cranes,
versatility and high lifting capacity

7131SC

A2				
		kg	3250	2330
		m	3,85	5,25

A3					
		kg	3115	2220	1610
		m	3,90	5,33	7,15

7161SC

A2		kg	4060	3010	2145
		m	3,80	5,13	7,08

A3		kg	3905	2905	2055	1555
		m	3,85	5,18	7,13	9,18

	Lift Moment	Slewing Angle	Working pressure	Oil tank capacity	Max Oil flow	Max lifting height	Standard crane weight
	tm	°	bar	l	l/m	m	kg
7130B							
A1	12,4	425	285	130	60	10	1545
A2	11,8	425	285	130	60	11,7	1665
A3	12,0	425	285	130	60	13,7	1780
A4	11,1	425	285	130	60	15,7	1870
A5	10,7	425	285	130	60	17,8	1955
7160B							
A1	15,8	425	280	130	60	10	1775
A2	15	425	280	130	60	11,7	1910
A3	14,5	425	280	130	60	13,7	2025
A4	14,2	425	280	130	60	15,7	2130
A5	13,7	425	280	130	60	17,8	2220
7131C							
A2	12	425	290	130	60	12,2	1820
A3	11,6	425	290	130	60	14,4	1935
A4	11,2	425	290	130	60	16,5	2040
A5	10,8	425	290	130	60	18,8	2140
A6	10,5	425	290	130	60	21	2230
7143C							
A2	12,4	425	305	130	60	12,2	1820
A3	11,9	425	305	130	60	14,4	1935
A4	11,6	425	305	130	60	16,5	2040
A5	11,2	425	305	130	60	18,8	2140
A6	10,8	425	305	130	60	21	2230
7153C							
A2	13,9	425	325	130	60	12,2	1820
A3	13,5	425	325	130	60	14,4	1935
A4	13,1	425	325	130	60	16,5	2040
A5	12,8	425	325	130	60	18,8	2140
A6	12,4	425	325	130	60	21	2230
7161C							
A2	15,3	425	300	130	60	12,2	1990
A3	14,9	425	300	130	60	14,4	2120
A4	14,4	425	300	130	60	16,5	2240
A5	14,0	425	300	130	60	18,8	2350
A6	13,6	425	300	130	60	21	2445
7173C							
A2	15,7	425	310	130	60	12,2	1995
A3	15,2	425	310	130	60	14,4	2125
A4	14,8	425	310	130	60	16,5	2245
A5	14,4	425	310	130	60	18,8	2355
A6	14,0	425	310	130	60	21	2450
7183C							
A2	17,3	425	330	130	60	12,2	1995
A3	16,8	425	330	130	60	14,4	2125
A4	16,4	425	330	130	60	16,5	2245
A5	16,0	425	330	130	60	18,8	2355
A6	15,6	425	330	130	60	21	2450
7130D							
A2	13,1	425	285	130	60	9,8	1485
A3	13	425	285	130	60	11,8	1585
A4	12,8	425	285	130	60	13,8	1675
7162D							
A2	16,4	425	290	130	60	9,8	1610
A3	16,3	425	290	130	60	11,8	1720
A4	16,0	425	290	130	60	13,8	1810
7131SC							
A2	12,5	425	300	130	60	10,6	1735
A3	12,1	425	300	130	60	12,9	1835
7161SC							
A2	15,4	425	300	130	60	11,9	1880
A3	15,0	425	300	130	60	12,9	2005

NEW AGE
13 - 16 tm Families



Quality and environmental certified



F.lli FERRARI CORPORATION S.p.A.

Via Einstein, 8
42028 Poviglio (RE) Italy
Tel. +39 0522/486308
Fax +39 0522/486330
info@flliferrari.it
marketing@flliferrari.it
www.flliferrari.com

Dealer

Data, descriptions, and illustrations pertain only and uniquely to models sold at the time of printing of this brochure. After the date of printing, this information is purely indicative and not binding upon F.lli Ferrari. Future modifications are solely at the discretion of F.lli Ferrari and are always in compliance with applicable and pertinent safety standards. To obtain updated data, descriptions, and illustrations, contact the manufacturer or your reseller. Cranes manufactured and/or marketed by F.lli Ferrari.

DATE OF PRINTING: 01/03/2016